

### Daily

- Clean Debris From Washbay
- Check Laserwash Is In Home Position
- Check Printer For Faults Overnight
- Check Computer For Faults I.E: 100 Enter(#) 1 Enter(#)
- Visually Inspect The Bay Equipment When A Car Is Being Washed For Any Faults
- Check That Product Is Spraying Correctly And Tips Are Not Blocked.
- Check Bridge And Overhead Swivel For Leaks.
- Check Solution Levels In Drums
- Check Tyres For Pressure With Hand.
- Drain Air Compressor

### Weekly

- Check Tyre Pressure's With Gauge (Set At 25psi)
- Check High And Low Pressure Gauges
- Spray CRC/WD-40 Onto Festoon Rollers
- Grease Machine Including The Straight And 90 Deg. Swivels
- Clean Reflective Strip (Not Applicable With Virtual Treadle)
- Check Over Machine For Abnormal Wear. Eg: Tyre Or Roller Wear
- Check Impact Proximity Switch (Pull Arch Sideways)
- Titration Test Of Low Pressure Soaps
- Check TDS Of Spot Free Water In Storage Tank (Must Be Below 25 ppm)
- Check Air Pressure Settings For Lexair Valves (Approx. 100 psi) And Overhead Manifold (Approx. 60psi).
- Clean Entry System
- Check Salt Level in Brine Tank
- Check Time and Day on Carbon Filter

### Monthly

- Clean Strainers In Pump Stand
- Clean Pump Stand Tanks (Siphon)
- Check Oil Level In General Pump (Call Prowash) Power OFF
- Check Belt Tension Power OFF
- Check Pressure Gauges On R/O Pre Filter (If Outlet Is More Than 15psi LESS Than Inlet Pressure, Change Filter)
- Check Hoses For Wear
- Clean Excess Grease From Machine
- Check Water Hardness
- Clean Covers On Machine

### 3 Monthly

- Check That Locknuts Are Tight On The Wall Brackets.
- Change Oil In Gear Boxes (3 In Total) (Call Prowash) Power OFF

### 6 Monthly

- Change Oil In General Pump (Call Prowash)
- Change R/O Pre Filter