



Self Serve Car Wash Equipment Maintenance Guide

EVERYDAY

- Check all chemical tanks for levels and colour (SuperSat)
- Hang all bay and vacuum hoses and check for damaged hoses or attachments
- Check level of Alkaline (powder) in SuperSat unit – if applicable
- Check correct operation of SuperSat unit – if applicable
- Clean bays (hose down)
- Clean site (Hako sweeper)
- Clean all bay hoses, guns and foam brush handles
- Check foam brush heads are tight on handle
- Visually check chemical levels in all drums
- Check operation of all in bay equipment. Eg: Hoses, swivels, brushes
- Pick up all rubbish on site and clean bins
- Drain compressor

ONCE A WEEK

- Clean vacuum waste bags and filter bags
- Empty notes from Change Machine and top up hoppers if necessary
- Check hot water temperature
- Check TDS of spot free in storage tank (Must be below 25ppm)
- Check salt level in Water Softener Brine Tank
- Check time and day on carbon filter
- Check fragrance liquid levels and fill as required (If applicable)
- Check shampoo liquid level (If applicable)
- Check vending machines and fill as required
- Clean all stainless steel equipment in plant room (WD-40)
- Clean vacuums (outside) and all hoses
- Check vacuum nozzles for wear
- Clean bay walls

EVERY MONTH

- Check oil level in pumps
- Check pressure gauges on R/O pre-filter (If outlet is more than 15psi LESS than inlet pressure, change filter)
- Wash vacuum filter bags (rotate with spares)
- Titration of chemicals
- Place a stock order
- Check water hardness



EVERY 3 MONTHS

- Clean all chemical tanks (siphon and drain)
- Clean all strainers in product tanks
- Clean all strainers in Hydrominders (main water)
- Check sludge levels in pits

EVERY 6 MONTHS

- Change oil in CAT/Hydro pumps
- Check vacuum brushes for wear
- Check tension of CAT/Hydro belts
- Change R/O pre-filter