

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

## 1.1 Product identifier

**Product name** 

## SUPERSAT HPH PLUS POWDER

SUPERSAT HPH PLUS POWDER (20KG) (FORMERLY)

#### 1.2 Uses and uses advised against

Uses VEHICLE CARE • VEHICLE CLEANING DETERGENT

#### 1.3 Details of the supplier of the product

Supplier name	DUBOIS CHEMICALS AUSTRALIA PTY LIMITED
Address	305 Frankston Dandenong Rd, Dandenong South, VIC, 3175, AUSTRALIA
Telephone	(03) 9768 3860
Email	sales@duboischemicals.com.au
Website	http://duboischemicals.com.au/

#### 1.4 Emergency telephone numbers

Emergency

13 11 26 (Poisons Information Centre)

## 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### **Physical Hazards**

Corrosive to Metals: Category 1

#### **Health Hazards**

Skin Corrosion/Irritation: Category 1A Serious Eye Damage / Eye Irritation: Category 1 Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)

#### **Environmental Hazards**

Not classified as an Environmental Hazard

#### 2.2 GHS Label elements

#### Signal word DANGER

**Pictograms** 



#### Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.



#### PRODUCT NAME SUPERSAT HPH PLUS POWDER

#### **Prevention statements** P234 Keep only in original packaging. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. **Response statements** P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician. P310 Specific treatment is advised - see first aid instructions. P321 P363 Wash contaminated clothing before reuse.

 P390
 Absorb spillage to prevent material damage.

 Storage statements
 P403 + P233
 Store in a well-ventilated place. Keep container tightly close

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.

#### Disposal statements

P501

Dispose of contents/container in accordance with relevant regulations.

#### 2.3 Other hazards

No information provided.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
PENTASODIUM TRIPHOSPHATE	7758-29-4	231-838-7	30 to 40%
SODIUM CARBONATE	497-19-8	207-838-8	15 to 25%
SODIUM METASILICATE ANHYDROUS	6834-92-0	229-912-9	15 to 25%
SODIUM SULPHATE	7757-82-6	231-820-9	10 to 20%
SODIUM HYDROXIDE	1310-73-2	215-185-5	5 to 10%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

## 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

Еуе	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator where an inhalation risk exists. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.



## PRODUCT NAME SUPERSAT HPH PLUS POWDER

## 4.3 Immediate medical attention and special treatment needed

CORROSIVE POISONING TREATMENT: Immediate treatment preferably in a hospital is mandatory. In treating corrosive poisoning, DO NOT INDUCE VOMITING; DO NOT ATTEMPT GASTRIC LAVAGE; and DO NOT ATTEMPT TO NEUTRALISE THE CORROSIVE SUBSTANCE. Vomiting will increase the severity of damage to the oesophagus as the corrosive substance will again come in contact with it. Attempting gastric lavage may result in perforating either the oesophagus or stomach. Immediately dilute the corrosive substance by having the patient drink milk or water. If the trachea has been damaged tracheostamy may be required. For oesophageal burns begin broad-spectrum antibiotics and corticosteroid therapy. Intravenous fluids will be required if oesophageal or gastric damage prevents ingestion of liquids. Long-range therapy will be directed toward preventing or treating oesophageal scars and strictures.

## 5. FIRE FIGHTING MEASURES

#### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

#### 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve flammable hydrogen gas in contact with some metals. May evolve sulphur oxides, phosphorus oxides and metal oxides when heated to decomposition.

#### 5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

#### 5.4 Hazchem code

- 2X
- 2 Fine Water Spray.
- X Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

#### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for disposal.

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate ventilation systems.

#### 7.3 Specific end uses

No information provided.



## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient	Reference	ppm	mg/m³	ppm	mg/m³
Sodium Carbonate (total dust)	SWA [AUS]		10		
Sodium hydroxide (peak limitation)	SWA [AUS]		2 (Peak)		

#### **Biological limits**

No biological limit values have been entered for this product.

## 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

#### PPE

Eye / Face	Wear a faceshield and dust-proof goggles.
Hands	Wear PVC or rubber gloves.
Body	Wear coveralls and rubber boots and a PVC apron.
Respiratory	Where an inhalation risk exists, wear a Class P1 (particulate) / N95 respirator. At high dust levels, wear an Air-line / Full Facepiece Supplied-Air Respirator (SAR) or a Full-face Class P3 (particulate) / N100 respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

normation on saore prijerear a	
Appearance	WHITE SOLID
Odour	FAINT ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	ALKALINE
Vapour density	NOT AVAILABLE
Relative density	NOT AVAILABLE
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

## **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

May be corrosive to metals.



## PRODUCT NAME SUPERSAT HPH PLUS POWDER

#### 10.2 Chemical stability

Stable under recommended conditions of storage.

## 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

## 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

## 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), metals, heat and ignition sources.

## 10.6 Hazardous decomposition products

May evolve sulphur oxides, phosphorus oxides and metal oxides when heated to decomposition.

## **11. TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects

Acute toxicity

Ingestion may result in severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

#### Information available for the ingredients:

Ingredient		Oral LD50	Dermal LD50	Inhalation LC50
PENTASODIUM TRIP	HOSPHATE	3100 mg/kg (mouse)		
SODIUM CARBONAT	SODIUM CARBONATE		> 2000 mg/kg (rat) (AICIS)	> 2000 mg/m³ (rat) (AICIS)
SODIUM METASILICA	ATE ANHYDROUS	770 mg/kg (mouse)		
SODIUM SULPHATE		5989 mg/kg (mouse)		
Skin	Causes severe burns. Con Effects may be delayed.	tact may result in irritatior	n, redness, pain, rash, dei	rmatitis and severe burns.
Еуе	Causes severe burns. Contact may result in irritation, lacrimation, pain, redness and corneal burns with possible serious eye damage.			ss and corneal burns with
Sensitisation	Not classified as causing skin or respiratory sensitisation.			
Mutagenicity	Not classified as a mutagen.			
Carcinogenicity	Not classified as a carcinoge	en.		
Reproductive	Not classified as a reproduct	tive toxin.		
STOT - single exposure	Over exposure to dust may result in mucous membrane irritation of the respiratory tract, coughing and bronchitis. High level exposure may result in intense thirst, ulceration, lung tissue damage, chemical pneumonitis and pulmonary oedema. Effects may be delayed.			
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure. Adverse effects are generally associated with single exposure.			s are generally associated
Aspiration	Not classified as causing as	piration.		

## **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Harmful effect due to pH shift. Discharge into the environment should be avoided.

#### 12.2 Persistence and degradability

Not expected to be persistent in the aquatic environment.

#### 12.3 Bioaccumulative potential

Not expected to bioaccumulate.

12.4 Mobility in soil

Soluble in water. Highly mobile in soils.

#### 12.5 Other adverse effects

Avoid contamination of drains and waterways.

# ChemAlert.

## 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Waste disposal

**posal** Collect without generating dust. Place in clean, sealed containers and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3262	3262	3262
14.2 Proper Shipping Name	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (contains sodium hydroxide, sodium metasilicate)	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (contains sodium hydroxide, sodium metasilicate)	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (contains sodium hydroxide, sodium metasilicate)
14.3 Transport hazard class	8	8	8
14.4 Packing Group	II	II	

#### 14.5 Environmental hazards

Not a Marine Pollutant.

#### 14.6 Special precautions for user

Hazchem code	2X
GTEPG	REFER
EmS	F-A, S-B

## **15. REGULATORY INFORMATION**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

#### Inventory listings AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt.

#### **16. OTHER INFORMATION**

Additional information RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).



#### PRODUCT NAME SUPERSAT HPH PLUS POWDER

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	Ab	bre	evi	ati	on	IS
---------------	----	-----	-----	-----	----	----

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m³	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
Report status	This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').	
	It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.	
	While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.	

Prepared by

**Risk Management Technologies** 5 Ventnor Äve, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmtglobal.com Web: www.rmtglobal.com

## [End of SDS]

